

## Features

- 3 5/6 Digits (6000 Counts)
- Auto Ranging
- True RMS
- ACV Freq., Measurement
- 600  $\mu$ A Range in Both AC & DC
- Auto Ranging Cap., Freq., & Temp., Tests
- A.P.O., NCV, D/H, REL, B/L & Torch
- A/V Continuity & Diode Test with Holster



### SPECIFICATIONS

<b>DC Voltage</b>	Range	600 mV, 6 V, 60 V, 600 V
	Basic Accuracy	$\pm$ (0.5 % rdg + 3 digits)
<b>AC Voltage (True RMS)</b>	Range	6 V, 60 V, 600 V
	Basic Accuracy	$\pm$ (0.8 % rdg + 5 digits). 40 Hz ~ 1 KHz Freq., Response.
<b>DC Current</b>	Range	600 $\mu$ A, 6000 $\mu$ A, 60 mA, 600 mA, 6 A, 10 A
	Basic Accuracy	$\pm$ (1 % rdg + 10 digits)
<b>AC Current (True RMS)</b>	Range	600 $\mu$ A, 6000 $\mu$ A, 60 mA, 600 mA, 6 A, 10 A
	Basic Accuracy	$\pm$ (1 % rdg + 10 digits). 40 Hz ~ 1 KHz Freq., Response.
<b>Resistance</b>	Range	600 $\Omega$ , 6 K $\Omega$ , 60 K $\Omega$ , 600 K $\Omega$ , 6 M $\Omega$ , 60 M $\Omega$
	Basic Accuracy	$\pm$ (0.8 % rdg + 4 digits)
<b>Capacitance</b>	Range	10 nF, 100 nF, 1 $\mu$ F, 10 $\mu$ F, 100 $\mu$ F, 200 $\mu$ F, 2 mF
	Accuracy	$\pm$ (3.5 % rdg + 20 digits)
<b>Frequency</b>	Range	10 Hz, 100 Hz, 1 KHz, 10 KHz, 20 KHz, 100 KHz, 2 MHz - Auto Ranging
	Basic Accuracy	$\pm$ (1 % rdg + 10 digits) Sens.: 1 Vrms & O/L Prot.: 250 V DC / AC rms.
<b>Temperature</b>	Range	- 20 $^{\circ}$ C ~ 1000 $^{\circ}$ C (-4 $^{\circ}$ F ~ 1832 $^{\circ}$ F)
<b>Other Facilities / Features</b>	NCV, Torch, ACV Freq., Measurement, A/V Continuity Test, Diode Test, LCD Back Light, Data Hold, REL Meas., Auto Power Off, Low Batt., Ind.	
<b>Accessories Supplied</b>	Holster (Installed), Test Leads, User Manual, Battery - 2 x AAA (Installed / Kept Aside) & Temperature Probe.	
<b>Dimension &amp; Weight</b>	146 x 72 x 50 mm & Approx. 235 gms. (With Batt. & Holster)	

\* All Specifications & appearances are subject to change without prior notice

